Environmental Transport and Fate of Alkylates



Alfredo A. Marchetti

Lawrence Livermore National Laboratory Energy and Environment Directorate

DOE Office of Fuel Development

Workshop on the Increased Use of Ethanol and Alkylates in Automotive Fuels in California

April 10 & 11, 2001

Oakland, California

Alkylate synthesis: basic reaction




Isobutene Isobutane Isooctane (2-Methylpropene) (2-Methylpropene) (2,2,4-Trimethylpentane)

The reaction is catalyzed with sulfuric acid at low temperature< 10°C.

Alkylate composition





Data from STRATCO

Percentages are in agreement with those presented by Durett *et al.* for a finished alkylate (*Anal. Chem.* **35** pp 637, 1963)

Physicochemical properties for MTBE, ethanol, benzene and isooctane



Fuel Compound

Property	MTBE	Ethanol	Benzene	Isooctane
MW (g/mol)	88.15	46.07	78.11	114.23
Boiling point (°C)	55.2	78.2	80.1	99.2
Density (g/mL)	0.741	0.789	0.879	0.69
K _{ow}	8.71	0.50	135	12,200
Vapor pressure†(kPa)	33.3	7.9	12.6	6.49
Solubility (mg/L)	51,000	Miscible	1,800	2.44
Henry's law [†] (Pa-m³/mol)	59.5	0.64	562	323,000

[†]at 25°C

Air



- Releases to the atmosphere
 - Incomplete combustion and evaporative emissions from vehicles and fuel delivery systems
 - Evaporation from direct spills on land and water
- Calculated rates of evaporation using two-film model for a pool of pure compound in mol/m²-h (Wind speed 1 m/s at 10 m from surface)

MTBE 140
 Benzene 57.6
 Ethanol 43.2
 Isooctane 25.2
 Water 23.0



Atmospheric reactions



Main degradation reaction

$$HO + RH R R + H_2O$$

- For alkanes with 2 to 8 carbons, k_{HO}~ (0.3—9) ? 10⁻¹² cm³ mol⁻¹ s⁻¹
- Methane k_{HO}=0.0084? 10⁻¹² cm³ mol⁻¹ s⁻¹, very long-lived, most abundant in atmosphere
- Ozone forming potential in the maximum incremental reactivity scale (Carter, 1994)

MIR [$g O_3/g$]


MTBE 0.62

Ethanol 1.34

Benzene 0.42

Isooctane 0.93

Olefins up to ~10



Water



- Alkylates solubility in water is very low (10⁻⁴—10⁻⁵ M)
 - Ethanol as cosolvent can increase the solubility of alkylates
 - E.g.: Calculations show that for an ethanol concentration in water of 10% [v] the solubility of isooctane would increase by ~1.5
- ◆ Alkylates have high Henry's law constants ☐ in air-water systems they concentrate mainly in the air phase
 - The mass transfer velocity based on the two-film model for surface waters is ~0.3 m/day[‡], for isooctane, benzene, and MTBE; in contrast, for ethanol, it is ~0.05 m/day [‡]

[‡]wind velocity at 10 m from surface = 1 m/s

- Rainout calculation
 - Calculation of concentration in rain water using a concentration in air of
 1 ppb [v] and assuming equilibrium

```
• Ethanol 7.33 ? g/L
```


Isooctane 0.000036 ? g/L

Relative impacts of atmospheric rainout of fuel compounds on shallow ground water



Baehr's model (1999) was used to simulate the impact of rainout onto a sandy soil with a depth of 5 m to the water table

The relative impacts on ground water are described by the ratio of the concentration of a fuel compound in ground water to its concentration in air




Degradation rate, 1/d

Impact to water or soil systems also depends on (bio)degradability, e.g., Predicted concentrations in a lake after a continuous, 7-day release of 40 kg/d



- Reference conditions are an epilimnion of 8 m and an average wind speed of 3 m/s
- With an assumed half-life of 24 hr, ethanol attains a substantially lower concentration in surface water than the other fuel compounds
- The water-to-air mass transfer of both MTBE and isooctane are limited by resistance in the water phase
- The estimated volatilization halflives for these two compounds are 15-16 days



Soils: distribution among phases




Soil Characteristics

Density 1.59 g/cm³ L/L **Porosity** 0.4 Water cont. 0.18 L/L 0.0075 f organic-carbon **Precipitation** 100 cm/y Infiltration rate 18 cm/y


Tranport and losses in soil can be estimated using Jury's model (1990) with corrections by Robinson (2000)

E.g.: Sandy soil with a buried 1-m deep and 30-cm thick source; source concentration is 1 ppm and concentration in air is zero



Concentration profiles in soil for a 1 ppm 30-cm wide 1-m deep input pulse after 5 days








Biodegradation of isooctane

- A laboratory experiment conducted by Solano-Serena (1998) used an unpolluted forest soil to incubate a gasoline solution. After 28 days at 30°C, 20 % of the isooctane was degraded. Benzene, in contrast, was completely degraded
- The corresponding degradation half-life is about 88 days for isooctane
- Based on the results of a field study of a contaminated aquifer by Nielsen (1996), it is likely that the *in-situ* degradation of isooctane will be considerably longer and will depend in part on the occurrence of certain natural microorganisms capable of degrading fuel hydrocarbons

Biodegradation: mineralization yields in unpolluted soil






Mineralization of individual hyrdrocarbons by native soil microflora after 34 days of incubation at 30°C. From Solano-Serena *et al.* (1998)

Biodegradation prediction (BIOWIN)





Probability of biodegradation by group contribution method: program BIOWIN v4.0 from the Syracuse Research Corporation. **Probability > 0.5** implies readily biodegradable

Summary



- Alkylates—mostly branched C8-alkanes
 - Low solubility in water
 - High Henry's law constant
 - Less dense than water
 - High K_{ow}
- Transport and fate in the environment
 - Surface releases
 - Air is the major sink; HO-oxidation with 2-3 days halflife
 - Moderate ozone forming potential compared to other gasoline components
 - Possibly minimal impact on waters
 - Subsurface releases
 - Depending on soil characteristics and source location significant migration to the atmosphere is possible
 - There is also strong absorption in the soil organic phase (high K_{ow})
 - Branched alkanes tend to be recalcitrant—only few experimental biodegradation studies